

DF6100-EP Doppler Portable Ultrasonic Flow Meter

Series DF6100-EP Doppler Portable Ultrasonic Flow Meter is designed to measure volumetric flow of within closed conduit, the pipe line must be full of liquids, and there must be a certain amount of air bubbles or suspended solids in liquid.

The Doppler ultrasonic flow meter can display flow rate and flow totalizer, etc., and is configured with 4-20mA, OCT outputs



Features:

- ◆ It is suitable for pipe sizes ranging from 40 to 4000mm
- ◆ For dirty liquids, a certain amount of air bubbles or suspended solids shall be contained
- ◆ Excellent low flow rate measurement ability, low to 0.05m/s
- ◆ A wide range of flow measurement, high flow rate can reach 12m/s
- ◆ High-temperature transducer is suitable to liquids of $-35^{\circ}\text{C} \sim 200^{\circ}\text{C}$
- ◆ Do not need to shut down the pipe flow when installing the transducers
- ◆ User-friendly configuration
- ◆ 4-20mA, OCT outputs
- ◆ Accuracy: 2.0% Calibrated span
- ◆ Rechargeable battery can work up to 50 hours

Applications:

- ◆ Raw sewage
- ◆ Activated sludge
- ◆ Ground water
- ◆ Pulp and paper slurries
- ◆ Chemical slurries
- ◆ Drainage
- ◆ Mining recirculation

Technical Parameters:**Specifications: Transmitter**

Measurement principle	Doppler ultrasonic
Resolution	0.25mm/s
Repeatability	0.2% of reading
Accuracy	0.5% -- 2.0% F.S.
Response time	2-60s for optional
Flow Velocity Range	0.05- 12 m/s
Liquid Types Supported	Liquids containing 100ppm of reflectors and at least 20% of the reflectors are larger than 100 micron.
Power Supply	AC: 85-265V
Enclosure type	Portable
Degree of protection	IP65 according to EN60529
Operating temperature	-20°C to +60°C
Housing material	ABS
Measurement Channels	1
Display	2 line x 8 characters LCD, 8-digit rate or 8-digit total (resettable)
Units	User Configured (English and Metric)
Rate	Rate and Velocity Display
Totalized	gallons, ft ³ , barrels, lbs, liters, m ³ ,kg
Communication	4-20mA,OCT output
keypad	6pcs buttons
Size	Transmitter:270X125X175mm
Weight	3kg

Specifications: Transducer

Transducers Type	Clamp-on
Degree of protection	IP65. IP67 or IP68 according to EN60529
Suited Liquid Temperature	Std. Temp.: -35°C~85°C for short periods up to 120°C High Temp.: -35°C~200°C for short periods up to 250°C
Pipe diameter range	40-4000 mm
Transducer Size	60(h)*34(w)*33(d)mm
Material of transducer	Aluminum for standard temp. sensor, peek for high temp. sensor
Cable Length	Std: 5m

Images:



Transmitter



Transducer



S-S Belt



Couplant



Soft Case

Configuration Code:

DF6100-EP	Portable Doppler Clamp-on Series Flowmeters
Power supply	
A	85-265VAC
Output Selection 1	
N	N/A
1	4-20mA
2	OCT
Output Selection 2	
Same as above	
Sensor Type	
D	Standard Clamp-on transducer (DN40-4000)
Transducer Temperature	
D	-35 ~ 85°C (for short periods up to 120°C)
H	-35 ~ 200°C
Pipeline Diameter	
DNX	e.g. DN40—40mm, DN4000—4000mm
Cable length	
5m	5m (standard 5m)
Xm	Common cable Max 300m (standard 5m)
XmH	High temp. cable Max 300m

DF6100-EP — **A** — **1** / **LDP** — **D** — **S** — **DN600** — **5m** (example configuration)